



HYBRID 9.5

PRODUCT SPECIFICATIONS

Technical Data

Type	Hybrid	Finish	Matte
Dimensions	1860mm (L) x 228mm (W)	Surface	Embossed
Plank Thickness	9.5mm	Wear Layer	0.5mm
Planks per Carton	4	Profile	Fold-Down Click-Lock
M ² per Carton	1.6963m ²	KG per Carton	22.3kg
M ² per Pallet	88.2076m ²	KG per Pallet	1,159.6kg
Installation Method	Floated on Sub-Floor	Surface Coating	Antibacterial UV Coating
Backing Thickness	2mm	Click System	5G Valinge

Performance

Standard

Slip Resistance	P3	AS 4586:2013
Fire Rating	CHF Value 9.3 kW/m ² Smoke Value 27%.min	AS ISO 9239.1-2003
Acoustic	L' _{nt,w} 38	ISO 717-2:2014
Total VOC	0.020mg/m ² /hr	ASTM D5116-17
Underfloor Heating	Suitable for Hydronic Underfloor Heating <i>under</i> 26°C	

Warranty

Residential	Lifetime (Structural) 25 years (Wear)	Commercial	15 Years
-------------	--	------------	----------



**Wear & Scratch
Resistant**




**100%
Waterproof**



**Antibacterial
Coating**



**Easy Install
& Repair**



**Noise
Insulating**